


Sensore di movimento infrarossi a lente piatta

Flat lens infrared motion sensor

M+



50-60 Hz - 230 Vac
Angolo di rilevazione 130°
Trimmer Time: attivazione carico da 10 secondi a 7 minuti regolabile
Trimmer Lux: regola la soglia di attivazione 6-500 lux
Distanza di rilevamento: max 5 m

Il sensore è adatto per carichi induttivi quali:
ventole, aspiratori e motori
Potenza massima 200W

50-60 Hz - 230 Vac
Detection angle 130°
Trimmer Time: shutdown delay adjustment from 10 seconds to 7 minutes
Lux Trimmer: set the activation threshold 6-500 lux
Maximum detecting distance: 5 m

The sensor is suitable for inductive loads such as:
fans, exhaust fans and motors
Max power 200W



CODICE	INCANDESCENZA	FLUORESCENZA	LED 230V	SOGLIA DI INTERVENTO	MAX DISTANZA RILEVAMENTO	ATTACCO	ANGOLO DI RIVELAZIONE	PESO
CODE	INCANDESCENT	FLUORESCENT	LED 230V	INTERVENTION THRESHOLD	MAX DETECTING DISTANCE	MOUNT	DETECTION ANGLE	WEIGHT
	W	W	W	Lux	m		gradi (°)	gr
KS321SE	1000	200	250	6-500	5	Keystone	130	30

ACCESSORI ADATTATORI

PAGINA 96