


# Relé ad impulsi meccanico modulare

Modular step relay



50-60 Hz - 12, 24, 230 Vac  
 Contenitore modulare in guida DIN  
 Carico nominale 16A - 250 Vac  
 Pulsante di comando a bordo

50-60 Hz - 12, 24, 230 Vac  
 Modular case in Din rail  
 Rated load 16A - 250 Vac  
 ON-Board push button



CODICE	TENSIONE	INCANDESCENZA	ALOGENA	FLUORESCENZA	LED 230V	PULSANTI LUMINOSI COLLEGABILI	CONTATTI	PESO
CODE	VOLTAGE	INCANDESCENT	HALOGEN	FLUORESCENT	LED 230V	CONNECTABLE ILLUMINATED PUSH-BUTTONS	CONTACT	WEIGHT
	Vac	W	W	W	W			gr
<b>RE012DI</b>	12	1000	700	350	100*	4	1 NO	85
<b>RE024DI</b>	24	1000	700	350	100*	4	1 NO	85
<b>RE230DI</b>	230	1000	700	350	100*	4	1 NO	85
<b>CO250RE</b>	1,5uF-250 Vac condensatore, consente di collegare fino a 25 pulsanti / capacitor, allow to connect max 25 illuminated push buttons							10