

Interruttore orario digitale giornaliero/settimanale


Daily/weekly digital time switch

Easy-1C+



IP20

-20°
+50°



50-60 Hz - 230 Vac
 Installazione su guida DIN
 Contenitore modulare autoestingente VO
 Uscita relè in scambio 16A
 Precisione ± 1 sec/giorno a 24° C
 Cambio automatico ora solare/legale
 Display LCD retroilluminato
 Configurazione semplice ed intuitiva
 Programmazione giornaliera/settimanale
 Intervallo minimo di programmazione 1/30 min
 Mantenimento dati in assenza di rete fino a 20 giorni (Supercapacitor)
 Blocco con pin a 4 cifre
 Commutazione allo zero di tensione per prolungare la vita del relè

50-60 Hz - 230 Vac
 DIN rail mounting
 Auto extinguish VO modular case
 16A SPDT changeover relay's contact
 Accuracy ± 1 sec/day at 24°C
 Automatic daylight-saving time change
 Backlighted LCD display
 Easy and intuitive configuration
 Daily/weekly scheduling
 Minimum setting time 1/30 min
 Storage data up to 20 days in case of power failure (Supercapacitor)
 4 digits lock code
 Zero crossing switching to increase relay life



CODICE	INCANDESCENZA	DUO/ELETRONICO	FLUORESCENZA	LED 230V	INTERVALLO MINIMO PROGRAMMAZIONE	CANALI	MODULO	PESO
CODE	INCANDESCENT	DUO/ELECTRONIC	FLUORESCENT	LED 230V	MINIMUM SETTING TIME	CHANNELS	MODULE	WEIGHT
	W	W	W	W	min	n	DIN	gr
OR213DI	1500	200	600	300*	1 / 30	1	2	120